REPORT	DOCUMENT	ATION PAGE

Form Approved OMB No. 0704-0188

OMB No. 0704-0188 Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS. 1. REPORT DATE (DD-MM-YYYY) 2. REPORT TYPE 3. DATES COVERED (From - To) **Technical Papers** 4. TITLE AND SUBTITLE 5a. CONTRACT NUMBER **5b. GRANT NUMBER** 5c. PROGRAM ELEMENT NUMBER 6. AUTHOR(S) 5d. PROJECT NUMBER 1011 5e. TASK NUMBER 0074 **5f. WORK UNIT NUMBER** 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) 8. PERFORMING ORGANIZATION REPORT Air Force Research Laboratory (AFMC) AFRL/PRS 5 Pollux Drive Edwards AFB CA 93524-7048 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) 10. SPONSOR/MONITOR'S ACRONYM(S) Air Force Research Laboratory (AFMC) 11. SPONSOR/MONITOR'S AFRL/PRS 5 Pollux Drive NUMBER(S) Edwards AFB CA 93524-7048 12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited. 13. SUPPLEMENTARY NOTES 14. ABSTRACT 15. SUBJECT TERMS 16. SECURITY CLASSIFICATION OF: 17. LIMITATION 19a. NAME OF RESPONSIBLE 18. NUMBER OF ABSTRACT OF PAGES PERSON

> Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std. 239.18

19b. TELEPHONE NUMBER

Leilani Richardson

(include area code)

(661) 275-5015

(iten enclose)

c. THIS PAGE

Unclassified

a. REPORT

Unclassified

b. ABSTRACT

Unclassified

10/16874

MEMORANDUM FOR PRS (In-House Publication)

FROM: PROI (STINFO)

15 August 2001

SUBJECT: Authorization for Release of Technical Information, Control Number: AFRL-PR-ED-AB-2001-172
David Barland, "Orthotropic Mechanical Properties of Uncoated and Ceramic-Coated Uniaxially-Compressed Carbon Cellular Porous Materials"

43rd AIAA/ASME/ASCE/AHS Struct., Struct. Dyn.& Materials Conf. (Denver, CO, 22-25 April 2002) (Deadline: 21 Aug 01)

(Statement A)

	or distribution restrictions, chnical sensitivity and/or economic sensitivity.
Signature	
Signature	
3. This request has been reviewed by the STINFO for: a.) check b) appropriateness of references, if applicable; and c.) formation comments:	at and completion of meeting clearance form if required
Signature	
4. This request has been reviewed by PR for: a.) technical adaptropriateness of distribution statement, d.) technical sensinational critical technology, and f.) data rights and patentable Comments:	tivity and economic sensitivity, e.) military/ ility

APPROVED/APPROVED AS AMENDED/DISAPPROVED

PHILIP A. KESSEL Date
Technical Advisor
Space and Missile Propulsion Division

20021119 106

Orthotropic Mechanical Properties of Uncoated and Ceramic-Coated Uniaxially-Compressed Carbon Cellular Porous Materials

Abstract

Porous cellular foams of moderate to high porosity (55%-95%) were investigated to determine orthotropic strength moduli and mechanical response. Uncoated porous samples consisted of reticulated vitreous carbon (RVC) rigidized by pyrolysis of flexible, open-pore organic precursor foams. The organic precursor's reference surface pore density was 100 pores-per-inch (ppi) before uniaxial compression. After compression, substrates contained 6% to 33% solid fraction. which corresponded in the thru-thickness direction to 200 ppi to 1100 ppi, respectively. Ceramic-overlaid samples were constructed by depositing silicon carbide (SiC) via chemical vapor infiltration (CVI) onto 600 ppi and 1000 ppi RVC substrates. The ceramic overlays added solid fractions of 5% and 12%, respectively. Compressive and tensile strengths were measured in-plane and thru-thickness for all materials. Results showed compressive crush strengths of the multi-layer porous materials to be bounded between theoretical strengths of solid RVC substrate and SiC-coated materials. Predictions from currently accepted cell anisotropy relations were compared to experiment and are shown to greatly over-predict the orthotropy due to uniaxial compression. The data may be applied to allow more precise design of components using ceramic-coated porous cellular materials.